

Air Aspirating Foam
Nozzle Air Foam Monitor

FIRE FRONT

Specification

These low expansion aerating air foam 3% nozzles are used in connection with fire hose and mainly used at hazardous storage tank, outdoor oil tank, airplane hangar, chemical plant, etc.

* NH, BSP, BS Quick, Machino Quick Connection available.
* Shoulder Strap available for 2½"(65) size.
* Foam nozzle type
* Option : Foam Adjuster (Metering Valve)



FF-17S FF-17Q FF-17PSQ FF-19MP FF-19MSQ FF-19MB

Model	Size	Flow rate at P=7KG/cm²	Material	Spray range at P=7KG/cm²	Length	Weight
FF - 17S	NH 1½"	330 L/min	Aluminum	28 m	590mm	1.1 KG
FF - 17	NH 1½"	305 L/min	Aluminum	25 m	597mm	1.2 KG
FF - 17PS	NH 1½"	305 L/min	Aluminum	25 m	630mm	2.3KG
FF - 19MP	NH 2½"	560 L/min	Aluminum	38 m	700mm	2.5 KG
FF - 19MSQ	Machino65	560 L/min	Aluminum	38 m	770mm	2.7 KG
FF - 19MB	NH 2½"	560 L/min	Aluminum	38 m	815mm	4.2 KG

FireFront Engineering LLP
Head Office:Suite 6, 5 Percy st., Fitzrovia, London, W1T 1DG, England
info@firefrontllp.com Email:.**sales@firefrontllp.com**